

Casing acc. to API 5CT

Outside diameter		Wall thickness		Nominal weight of threaded with coupling			Grade	Type of thread
in	mm	inch	mm	lb/ft	kg/m	kg/ft		
4 1/2	114,3	0,205	5,21	9,5	14,14	4,31	J,K	STC
		0,224	5,69	10,5	15,69	4,76	J,K	STC, BTC
		0,25	6,35	11,6	17,26	5,26	J,K,N,L,C,P	STC, LTC, BTC
		0,29	7,37	13,5	20,19	6,12	N,L,C,P	LTC, BTC
		0,337	8,56	15,1	22,47	6,85	P	LTC, BTC
5	127	0,22	5,59	11,5	17,11	5,22	J,K	STC
		0,253	6,43	13	19,35	5,9	J,K	STC, LTC, BTC
		0,296	7,52	15	22,32	6,8	J,K,N,L,C,P	STC, LTC, BTC
		0,362	9,19	18	26,79	8,16	N,L,C,P	LTC, BTC
5 1/2	139,7	0,244	6,2	14	20,83	6,35	J,K	STC
		0,275	6,98	15,5	23,07	7,03	J,K	STC, LTC, BTC
		0,304	7,72	17	25,3	7,71	J,K,N,L,C,P	STC, LTC, BTC
		0,361	9,17	20	29,76	9,07	N,L,C,P	LTC, BTC
		0,415	10,54	23	34,23	10,43	N,L,C,P	LTC, BTC
6 5/8	168,3	0,288	7,32	20	29,76	9,07	J,K	STC, LTC, BTC
		0,352	8,94	24	35,72	10,89	J,K,N,L,C,P	STC, LTC, BTC
		0,417	10,59	28	41,67	12,7	N,L,C,P	LTC, BTC
		0,475	12,06	32	47,62	14,52	N,L,C,P	LTC, BTC
7	177,8	0,272	6,91	20	29,76	9,07	J,K	STC
		0,317	8,05	23	34,23	10,43	N,L,J,K,C	STC, LTC, BTC
		0,362	9,19	26	38,69	11,79	J,K,N,L,C,P	STC, LTC, BTC
		0,408	10,36	29	43,16	13,15	N,L,C,P	LTC, BTC
		0,453	11,51	32	47,62	14,52	N,L,C,P	LTC, BTC
		0,498	12,65	35	52,09	15,88	N,L,C,P	LTC, BTC
7 5/8	193,7	0,3	7,62	24	35,72	10,89	J,K	STC
		0,328	8,33	26,4	39,29	11,98	J,K,N,L,C	STC, LTC, BTC
		0,375	9,52	29,7	44,2	13,47	N,L,C,P	LTC, BTC
		0,43	10,92	33,7	50,12	15,29	N,L,C,P	LTC, BTC
		0,5	12,7	39	58,04	17,69	N,L,C,P	LTC, BTC
8 5/8	219,1	0,304	7,72	28	41,67	12,7	J,K	STC
		0,352	8,94	32	47,62	14,52	J,K	STC, LTC, BTC
		0,4	10,16	36	53,57	16,33	J,K,N,L,C	STC, LTC, BTC
		0,45	11,43	40	59,53	18,14	N,L,C,P	LTC, BTC
		0,5	12,7	44	66,48	19,96	N,L,C,P	LTC, BTC

Casing acc. to API 5CT

Outside diameter		Wall thickness		Nominal weight of threaded with coupling			Grade	Type of thread
in	mm	inch	mm	lb/ft	kg/m	kg/ft		
9 5/8	244,5	0,352	8,94	36	53,57	16,33	J,K	STC, LTC, BTC
		0,395	10,03	40	59,53	18,14	J,K,N,L,C	STC, LTC, BTC
		0,435	11,05	43,5	64,74	19,73	N,L,C,P	LTC, BTC
		0,472	11,99	47	69,94	21,32	N,L,C,P	LTC, BTC
		0,545	13,84	53,5	79,61	24,27	N,L,C,P	LTC, BTC
10 3/4	273,1	0,35	8,89	40,5	60,27	18,37	H	STC
		0,35	8,89	40,5	60,27	18,37	J,K	STC, BTC
		0,4	10,16	45,5	67,71	20,64	J,K	STC, BTC
		0,45	11,43	51	75,89	23,13	J,K	STC, BTC
		0,495	12,57	55,5	82,59	25,17	N	STC, BTC
11 3/4	298,5	0,333	8,46	42	62,5	19,05	H	STC
		0,375	9,52	47	69,94	21,32	J,K	STC, BTC
		0,435	11,05	54	80,36	24,5	J,K	STC, BTC
		0,489	12,45	60	89,29	27,22	J,K	STC, BTC
13 3/8	339,7	0,33	8,38	48	71,43	21,77	H	STC
		0,38	9,65	54,5	81,1	24,72	J,K	STC, BTC
		0,43	10,92	61	90,78	27,67	J,K	STC, BTC
		0,48	12,19	68	101,19	30,84	J,K	STC, BTC
		0,514	13,06	72	107,14	32,66	N	STC, BTC
16	406,4	0,438	11,13	75	111,7	34,05	J/K55	STC, BTC, LTC
		0,495	12,57	84	125,1	38,13		STC, BTC, LTC
20	508	0,438	11,13	94	140	42,67	J/K55	STC, BTC, LTC
		0,5	12,7	106,5	158,6	48,34	J/K55	STC, BTC, LTC
		0,635	16,13	133	198,1	60,38	J/K55	STC, BTC, LTC